

# Borates Plus

1101 S. Orange Blossom Trail  
Apopka, FL 32703

Safety Data Sheet

## Ulexite

Revised: 4/23/2015

### 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

#### Product identifier

Commercial Name: Ulexite 15.0% Boron  
Chemical Name: Ulexite  
CAS No: 1319-33-1  
Chemical Family: Inorganic Borates

#### Substance's identified relevant applications and inadvisable uses:

##### Advisable uses:

- Agriculture

##### Uses advised against:

- Not specified

#### Supplier information from the Safety Information Sheet:

Producer: Borates Plus  
1101 S. Orange Blossom Trail  
Apopka, FL 32703  
Tel: 724-332-1446 Fax: 440-398-0476

**Emergency line: CHEMTREC - Within USA and Canada: 1-800-424-9300**

### 2. HAZARDS IDENTIFICATION

Ulexite is a brown odorless, granular substance that is not flammable, combustible, or explosive, and it presents no unusual hazard if involved in a fire. Ulexite presents little or no hazard (to humans) and has low acute oral and dermal toxicities.

#### Classification of the substance

##### GHS-US classification –

Health: 0  
Fire: 0  
Reactivity: 0

**Label elements:**  
**WARNING**

H316: Causes mild skin irritation  
H320: Causes eye irritation  
P103: Read label before use  
P264: Wash hands thoroughly after handling

### 3. COMPOSITION

Chemical Name: Ulexite  
CAS No: 1319-33-1  
Chemical Formula:  $\text{CaNaH}_{12}(\text{BO}_3)_5 \cdot 2\text{H}_2\text{O}$   
Chemical Family: Inorganic Borates

### 4. FIRST-AID MEASURES

**IF INHALED:** No specific treatment is necessary since Ulexite is not likely to be hazardous by inhalation. Prolonged exposure to dust levels in excess of regulatory limits should always be avoided.

**IF IN EYES:** Use eye wash fountain or fresh water to cleanse eye. If irritation persists for more than 30 minutes, seek medical attention.

**IF ON SKIN:** Wash with soap and water.

**IF SWALLOWED:** Swallowing less than one teaspoon will cause no harm to healthy adults. If larger amounts are swallowed, give two glasses of water to drink and seek medical attention.

**NOTE TO PHYSICIANS:** Observation only is required for adult ingestion of less than 6 grams of Ulexite. For ingestion in excess of 6 grams, maintain adequate kidney function and force fluids. Gastric lavage is recommended for symptomatic patients only. Hemodialysis should be reserved for massive acute ingestion or patients with renal failure. Ulexite analyses of urine or blood are only useful for documenting exposure and should not be used to evaluate severity of poisoning or to guide treatment. (For further information: Litovitz T.L., Norman, S.A., Veltri, J.C. Annual Report of the American Association of Poison Control Centers Data Collection System. Am. J. Emerg. Med. 1986; 4:427-458)

### 5. FIRE-FIGHTING MEASURES

**Fire Extinguishing Media:** Use any means suitable for extinguishing fire.

**Hazards:** Not considered to be a fire hazard, because Ulexite is not flammable, combustible or explosive. The product is itself a flame retardant.

**Recommendations for fire-fighters:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

**Flammability Classification (29CFR 1910.1200):** Non-flammable solid.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protection, equipment and emergency procedures:

Personal protection equipment: No personal protective equipment is needed to clean up land spills.

Emergency procedures: Unnecessary

### Environment related precautions:

- Prevent product from entering sewers and watercourses.
- Place containers to eliminate collected residues according to the existing regulations.
- Ulexite is a water-soluble brown powder that may cause damage to trees or vegetation by root absorption.

### Methods and materials for containment and cleaning material:

#### Cleaning

Collect with a vacuum, broom, or shovel and use a container which meets the local regulations when discarding. Avoid polluting adjacent water when undergoing cleaning and the elimination of ground spills.

#### Spilling in water:

- Prevent the solution from being consumed or from polluting water or effluents.
- Ulexite will cause localized contamination of surrounding waters depending on the quantity dissolved. At high concentrations some damage to local vegetation, fish and other aquatic life may be expected.

Ulexite is a non-hazardous waste when spilled or disposed of, as defined in the Resource Conservation and Recovery Act (RCRA) regulations (40 CFR 261).

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Handle the product far away from sewers, surface and underground water and water sources for human consumption.

### Safe Storing Conditions:

- Though Ulexite does not require any special precautions, it is sensitive to moisture and will cake. Therefore, the bags should be kept tightly sealed and be stored indoors in a dry environment. Also, the bags should be rotated on a “first-in first-out” basis. Good housekeeping procedures should be followed to minimize dust generation and accumulation.
- **Storage Temperature:** Room Temperature (72F)
- **Storage Pressure:** Atmospheric
- **Special Sensitivity:** Moisture (Caking)

## 8. PERSONAL PROTECTION

**Occupational Exposure Limits:** Ulexite is listed/regulated by OSHA, Cal OSHA and ACGIH as “Particulate Not Otherwise Classified” or “Nuisance Dust.”

- OSHA:PEL -15 mg/m<sup>3</sup> total dust  
-5 mg/m<sup>3</sup> respirable dust
- ACGIH:TIV -10 mg/m<sup>3</sup>
- Cal OSHA:PEL -10 mg/m<sup>3</sup>
- PEL= “Permissible Exposure Limit”
- TLV= “Threshold Limit Value”

**Engineering Controls:** Use local exhaust ventilation to keep airborne concentrations of Ulexite dust below permissible exposure levels.

**Individual Protection Measures:** Where airborne concentrations are expected to exceed exposure limits, NIOSH/MSHA certified respirators must be used. Eye goggles and gloves are not required for normal industrial exposures, but may be warranted if environment is excessively dusty.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Brown granular solid
<b>Odor:</b>	Odorless.
<b>Solubility:</b>	0.46% by wt. (25°C)
<b>Bulk Density:</b>	50 lbs/ft <sup>3</sup>
<b>Specific Gravity:</b>	2.4

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Ulexite is a stable product, but when heated it loses water.

**Incompatible Materials:** Ulexite reacts as a weak acid which may cause corrosion of base metals. Reaction with strong reducing agents such as metal hydrides or alkali metals will generate hydrogen gas which could create an explosive hazard.

## 11. TOXICOLOGICAL INFORMATION

**Ingestion (Acute Oral Toxicity):** May cause gastrointestinal disturbances, nausea, vomiting, diarrhea.

**Skin (Acute Dermal Toxicity):** May cause skin redness or peeling with prolonged or repeated contact. Ulexite is not absorbed through intact skin.

**Primary Skin Irritation Index:** 0 (zero) Ulexite is non-corrosive.

**Eye:** Abrasive effects of dust may cause redness and blurred vision.

**Inhalation:** Dust may irritate upper respiratory tract (nose, throat)

**Chronic Effects:** No information available.

## 12. ECOLOGICAL INFORMATION

**Phytotoxicity:** Although boron is an essential micronutrient for healthy growth of plants, it can be harmful to boron-sensitive plants in higher quantities. Care should be taken to minimize the amount of Ulexite released to the environment.

**Fish Toxicity:**

Rainbow Trout (*S. gairdneri*)

24 day LC50=150.0 mg B/L

36 day NOEC-LOEC=0.75-1 mg B/L

Goldfish (*Carassius auratus*)

7 day NOEC-LOEC=26.50 mg B/L

3 day LC50=178 mg B/L

**Persistence/Degradation:** Boron is naturally occurring and ubiquitous in the environment.

**Soil Mobility:** Ulexite is soluble in water and is leachable through normal soil.

## 13. DISPOSAL CONSIDERATIONS

**Disposal Guidance:** Small quantities of Ulexite can usually be disposed of at Municipal Landfill sites. No special disposal treatment is required, but refer to state and local regulations for applicable site-specific requirements. Tonnage quantities of product are not recommended to be sent to landfills. Such products should be re-used for an appropriate application. RCRA (40 CFR 261): Ulexite is not listed under any sections of the Federal Resource Conservation and Recovery Act (RCRA).

## 14. TRANSPORT INFORMATION

**DOT Hazardous Material Classification:** Ulexite is not a U.S. Department of Transportation (DOT) Hazardous Material.

**DOT Hazardous Substances Classification:** Ulexite is not a DOT Hazardous Substance.

**International Transportation:** Ulexite has no U.N. number and is not regulated under any international rail, highway, water or air transport regulations.

## 15. REGULATORY INFORMATION

**RCRA:** Ulexite is not listed as a hazardous waste under any sections of the Resource Conservation and Recovery Act or regulations (40 CFR 261 et seq.)

**Superfund:** CERCLA/SARA. Ulexite is not listed under CERCLA (the Comprehensive Environmental Response Compensation and Liability Act) or its 1986 amendments, SARA (Superfund Amendments and Reauthorization Act), including substances listed under Section 313 of SARA, Toxic Chemicals, 42 USC 11023, 40 CFR 372.65; Section 302 of SARA, Extremely Hazardous Substances, 42 USC 11002, 40 CFR 355; or the CERCLA Hazardous Substances list, 42 USC 9604, 40 CFR 302.

**Safe Drinking Water Act:** Ulexite is not regulated under the SDWA, 42 USC 300g-1, 40 CFR 141 et seq. Consult state and local regulations for possible water quality advisories regarding boron. Clean Water Act (Federal Water Pollution Control Act): 33 USC 1251 et seq. (a) Ulexite is not itself a discharge covered by any water quality criteria of Section 304 of the CWA, 33 USC 1314.

(b) It is not on the Section 307 List of Priority Pollutants.

(c) It is not on the Section 311 List of Hazardous Substances, 33 USC 1321, 40 CFR 116.

**IARC:** The International Agency for Research on Cancer (of the World Health Organization) does not list or categorize Ulexite as a carcinogen.

**OSHA Carcinogen:** Ulexite is not listed.

**California Proposition 65:** Ulexite is not listed on any Proposition 65 lists of carcinogens or reproductive toxicants.

**Federal Food, Drug and Cosmetic Act:** Pursuant to 21 CFR 175.105, 176.180 and 181.30, Ulexite is approved by the FDA for use in adhesive components of packaging materials, as a component of paper coatings on such materials, or for use in the manufacture thereof, which materials are expected to come in contact with dry food products.

**CONEG Model Legislation:** Ulexite meets all the CONEG requirements relating to heavy metal limitations on components of packaging materials.

## 16. OTHER INFORMATION

SDS updated on: 4-23-2015